

Highly durable solvent based wood stain in various colors.
For interior and exterior use.



Product Features: Developed especially to resist extreme climate conditions. Contains active agents to prevent mould development. Fast drying. A unique transparency that highlights the natural properties and texture of the wood. For interior and exterior use.

Recommended Uses: Recommended for application on interior and exterior wooden surfaces, such as pergolas, garden furniture, roof frames, wooden fences, doors and door frames.

Technical Data:

Product code (SKU): 485-XXX ready to use colors, 485-100 clear glossy, 485-200 clear matt.

Color: 11 ready to use colors

Gloss: Satin, clear glossy (Varnit 100), clear matt (Varnit 200)

Calculated coverage *: 15 sqm./liter (in one coat)

Recommended dilution: A ready to use wood stain. If necessary, Tambour mineral white spirit.

Drying times: Touch **: 1 hour | Recoat: 24 hours | Final: 24 hours

Shelf life: 24 months

Package size	Quantity per pallet
0.25 liter	1440
0.75 liter	576
2.5 liters	210
4.5 liters	100
18 liters	27

Surface preparation and system recommendation:

New, Unpainted Wood:

Remove any dust, dirt and grease stains. Ascertain that the surface is dry. Sand with sandpaper 0 or 360 and clean off sanding dust. Apply a first coat of Varnit for Wood. Allow drying to a hard coat. Sand again with sandpaper 0 or 360 and clean off sanding dust. Apply another coat (until a satin finish is obtained). Ascertain complete drying between coats.

Old, Varnish Painted Wood:

Remove any old, loose and peeling coats and paint residue. Clean off dirt and dust. Ascertain that the surface is dry. Sand with sandpaper 0 or 360 and clean off sanding dust. Apply a first coat of Varnit for Wood.

Allow drying to a hard coat. Sand again with sandpaper 0 or 360 and clean off sanding dust. Apply another coat (until a satin finish is obtained). Ascertain complete drying between coats.

Notice: To obtain high exterior durability, apply the clear lacquers (Varnit for Wood 100, Varnit for Wood 200) only on colored Varnit for Wood. Darker colors provide better protection. To change the final finish and gloss and to provide additional protection, use clear lacquers: Varnit for Wood 100 for glossy finish or Varnit for Wood 200 for matt finish.

Application: A ready to use wood stain. Stir well before application and while painting.

When needed, thin Varnit for Wood 100 or Varnit for Wood 200 with Tambour Mineral White Spirit by 5%-10%.

Brush Application: Apply along the wood grain.

Sponge Application: apply several coats, to provide the required protection to the wood. Apply several coats until a satin gloss is obtained.

Cleanup and storage: Clean work tools with mineral white spirit, immediately after use. Pour a thin layer of mineral white spirit on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

Cautions: The paint is inedible, flammable, keep out of reach of children. Avoid contact with skin and eyes. Use in a well ventilated area only. Avoid inhaling the lacquer or its vapors. Specific information regarding the product is available in the safety manual (MSDS). Wash your hands with water and soap after completing application.

General notes: Do not apply when the wall is wet or when rain is expected for about 72 hours before and after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.