

Water based Polyurethane Varnit - Highly durable wood varnish

Tambour

Polyurethane water based acrylic wood varnish designed to protect wooden surfaces.
For Interior and exterior use.



Product Features: Highly durable. The wood varnish is designed to protect wood surfaces and maintain the natural texture of the wood. Fast drying. Easy to apply. Free of lead and chromates. Certified eco-friendly.

Recommended Uses: Recommended for application on interior and exterior wooden surfaces, such as pergolas, garden furniture, roof frames, wooden fences, doors, door frames, children's furniture and toys.

Technical Data:

Product code (SKU):	786-050
Color:	Transparent
Gloss:	Satin gloss
Calculated coverage *:	New, unpainted wood: 6-9 sqm./liter (in one coat) Painted wood: 13-16 sqm./liter (in one coat)
Recommended dilution	Water (see recommendation in "Application" section)
Drying times:	Touch **: 1 hour Recoat: 2-3 hours Final: 24 hours
Shelf life:	24 months

Package size	Quantity per pallet
0.25 liter	1440
0.75 liter	576

Surface preparation and system recommendation:

Do not apply on wet wood.

New, Unpainted Wood and/or Painted Wood in Good Condition:

Remove any dust, dirt and grease stains. Sand with sandpaper 0 or 360 and clean off sanding dust then apply Water Based Polyurethane Varnit.

Notice: To obtain high durability and maximum protection from UV radiation, apply the Water Based Polyurethane Varnit over Water Based tinted Varnit.

Application: Stir the wood stain well before application and while painting.

The wood stain appears to have a milky white color in its can and turns transparent once it is dry.

www.tambourpaints.com

Soft brush application: Apply along the wood grain. Dilute the wood varnish with about 25% of water for the first coat to ensure good absorption in the wood. Apply the next coat without dilution. Apply several coats until a satin gloss is obtained.

It is recommended to apply three coats. Between the coats, sand the surface lightly using sandpaper 0. The last coat should not be sanded.

Cleanup and storage: Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and well ventilated place.

Cautions: The paint is inedible; any work that includes application and use of this product shall be performed according to the applicable Safety, Health and Environmental regulations. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS). Avoid inhaling the paint or its vapors.

General notes: Do not apply when the wall is wet and/or rain is expected for about 72 hours before or after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.