

High quality, water based acrylic paint for elegant finish.
Interior and exterior eggshell finish paint
with excellent coverage and leveling.
In accordance with IS 1945 and certified eco-friendly.



Product Features: This paint provides an elegant look. With exceptional coverage, breathing paint, free of lead and chromates.

Recommended Uses: Interior and exterior plastered, concrete and bricks walls.

Technical Data:

Product code (SKU): 723-801 White, 723-802 Base P,
723-803 Base T, 723-804 Base D, 723-805 Base A

Color: White and 1200 colors from Tambour Spectrum fan deck

Gloss: Eggshell

Calculated coverage *: 13-14 sqm./liter (In two coats for White and Base P) |
7-8 sqm./liter (In two coats for the other bases)

Recommended dilution: Water (see recommendation in "Application" section)

Drying times: Touch **: 1 hour | Recoat: 2 hours | Cleaning and washing: 7 days

Shelf life: 24 months.

Package size	Quantity per pallet
18 liters	36
15 liters	36
11 liters	48
5 liters	64
3 liters	80
1 liters	100

Surface Preparation and System Recommendation:

Interior Whitewashed Surfaces:

Remove any loose, flakey, peeling lime or excessively thick layers. Sand with sandpaper to a smooth surface. Clean off dust thoroughly. Apply one coat of Bonderol Super Primer. Allow drying to a hard coat (about 4 hours) and apply two coats of Supercryl 2000. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

Painted Interior Walls:

Remove any old, loose and peeling paint. Apply one coat of Bonderol Super Primer on the peeling paint areas. Smooth the surface using readymade joint compound – Magic Bond Super (for interior applications only), and apply one coat of Bonderol Super Primer on it. Allow drying to a hard coat. Apply 2-3 coats of Supercryl 2000. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

New, Unpainted, Plastered Interior Walls:

Smooth the surface lightly using sandpaper. Remove dust and fill holes with Calcimo X. To obtain a smooth surface, apply 1-2 coats of Tambourfill diluted by 5%-10% of water and allow drying to a hard coat (about 4 hours). Apply first coat of Supercryl 2000 diluted by 15%-20% of water. For an additional coat dilute the paint with water by 10%-15% .Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

New Concrete and Cement Plaster Surfaces:

Paint can be applied only after the plaster is completely cured (about one month or more after application). Remove dust and apply one coat of Exterior Bonding Primer diluted by Tambour Mineral White Spirit. Allow drying for 24 hours at least. Apply 2-3 coats of Supercryl 2000. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

Painted Exterior Walls:

Clean the wall with water in a pressure of 120atm, and remove any loose and peeling paint. Apply one coat of Exterior Bonding Primer diluted by Tambour Mineral White Spirit. Allow drying for 24 hours. Apply 2-3 coats of Supercryl 2000. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

New Plastered Walls:

Apply 2-3 coats of Supercryl 2000. In a case the wall was repaired with readymade joint compound, apply one coat of Bonderol Super Primer on the repaired areas, before applying Supercryl 2000.

Application: Stir the paint well before application and while painting.

Apply using a brush/ Roller/ Airless: Dilute the paint with water for the first coat by 15% - 20% and stir well. Dilute the paint with water for an additional coat by 10%-15%. Apply 2-3 coats, according to the surface type. If the product is applied using an Airless piston spray device, dilute with up to 30% of water.

Cleanup and Storage: Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

Cautions: The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

General Notes: Do not apply when the wall is wet or when rain is expected and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.