

High quality water based acrylic paint.  
Interior matt finish paint resistant to fungus and mould.  
Especially designed for wet rooms such as bathrooms.  
In accordance with IS 809 and certified eco-friendly.



**Product Features:** Provides protection against fungus and mould. Odour free, washable, breathable, free of lead and chromates.

**Recommended Uses:** Interior surfaces such as: concrete, brick, cement, plasterwork walls and ceilings, gypsum boards, bathrooms, kitchens and living rooms. Also suitable for painting concrete, cement plaster and wood surfaces painted with water diluted paints.

## Technical Data:

**Product code (SKU):** 724-801 White, 724-802 Base P

**Color:** White and colors from Tambour fan decks (for base P)

**Gloss:** Matt

**Calculated coverage \*:**15-16 sqm./liter (In two coats)

**Recommended dilution:** Water (see recommendation in "Application" section)

**Drying times:** Touch \*\*: 1 hour | Recoat: 2 hours | Cleaning and washing: 72 hours

**Shelf life:** 24 months

Package size	Quantity per pallet
5 liters	64
1 liters	576

## Surface preparation and system recommendation:

### Interior Moldy Surfaces:

**Attention:** Supercryl Acrynol prevents mould and fungi development on clean surfaces, but it does not destroy existing mould and fungi. Therefore, if the surface to be painted is already

contaminated, clean it thoroughly before painting. Clean by rinsing the surface with Fungicheck solution, diluted with water (see application instructions of Fungicheck solution). Start painting only after the surface has been thoroughly rinsed with water and dried. Once the surface is prepared, apply the paint according to the application instructions for clear surfaces.

### Interior Surfaces Uninfected by Mold:

Stir the paint well. Repair defects using Glue Putty 2000. Apply first coat of Supercryl Acrynol, diluted by 20% of water and allow drying. Apply two additional coats of Supercryl Acrynol, diluted by 5%-15% water. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

### Interior Whitewashed Surfaces:

Remove any loose, flakey, peeling lime or excessively thick layers. Repair defects using Glue Putty 2000. Apply one coat of Bonderol Super Primer diluted according to instructions and allow drying. Apply two additional coats of Supercryl Acrynol diluted by water. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

**Application:** Stir the paint well before application and while painting.

**Roller/ Brush/ Pad application:** Dilute the paint with water for the first coat by 15% - 20% and stir well. Dilute the paint with water for an additional coats by 10%-15%.

To obtain a uniform finish, apply the paint until complete coverage is received.

**Cleanup and storage:** Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and well ventilated place, below 35°C.

**Cautions:** The paint is inedible; the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

**General notes:** Do not apply when the wall is wet or when rain is expected for about 72 before or after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

\* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

\*\* At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.