

Metallic effect that provides a wild dune look for interior walls.

Available in various textures:

Pearlato – semi-opaque pearl look,

Oro – semi-opaque gold look,

Natural – semi-opaque look in desert shades,

White Pearl – white look and 4 bright white shades.



**Product Features:** Acrylic water based effect, ready to use product. Environment and user friendly.

**Recommended Uses:** Wild dune look effect, for easy and fast application on interior walls, painted with acrylic paint.

### Technical Data:

<b>Product name:</b>	Safari Pearlato	Safari Oro	Safari Natural	Safari White Pearl
<b>Product code (SKU):</b>	739-406	739-407	739-403	739-435
<b>Color:</b>	Silvery pearl + 15 shades from given collection. Base SP	Gold + 6 shades from given collection. Base SO	Pastel shades from given collection. Base SW	White + 4 shades from given collection. Base WSP
<b>Gloss:</b>	Satin	Satin	Matt-satin	Satin

**Calculated coverage \*:** 4-6 sqm./kg

**Recommended dilution:** Ready to use – do not dilute

**Drying times:** Touch \*\*: 2 hours | Final: 24 hours

**Shelf life:** 24 months

<b>Package size</b>	<b>Quantity per pallet</b>
4.5 Kg	160

**Surface Preparation and System Recommendation:** Remove any old, loose and peeling paint. Clean the wall from dirt and dust. Apply one coat of Quartz Primer in a similar shade to the chosen Safari shade. If the surface is painted with lime paint, then apply one coat of Bonderol Super before applying the Quartz Primer (738-501). Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

**Application:** Stir the paint well before application and while painting.

**To obtain the wild dune look on a smooth background:**

It is recommended to apply first on a small area and then choose the preferred texture.

Dip a brush (3" – 4" wide) in the paint container. Apply a small quantity of the paint on the wall in wide crisscross movements. After covering a defined area, continue to 'play' in a free hand with the paint on the wall, applying it repeatedly, until islands of dune-like texture are created next to smooth areas (hills and ravines). It is recommended to apply over a diagonal section of about 0.5 sqm. at a time, and ensure complete coverage. It is recommended to step away from the wall occasionally during the application, to view the entire wall. If you wish to obtain a higher paint density, continue to load the brush with paint and apply. Watch out for areas with excessive amount of paint. If it tends to run, continue to spread the paint. Use a dry brush to brush lightly in one direction, to obscure brush marks.

**Notice:** Do not accelerate drying with a ventilator or a heat blower, to prevent splintering and cracks. The final shade and look is affected by the direct lighting on the wall and by the reflection of the light on the wall.

**Cleanup and Storage:** Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

**Cautions:** The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

**General Notes:** Do not apply when the wall is wet or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

\* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

\*\* At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.