

A decorative paint for inside walls.  
Provides a prestigious velvet-like finish as cashmere fabric.



---

**Product Features:** Thick, water based, ready to use product.

---

**Recommended Uses:** Water based paint for easy and fast application on interior walls, painted with acrylic paint.

---

### Technical Data:

**Product code (SKU):** 795-406

**Color:** Silvery pearl + 20 shades from given collection

**Gloss:** Silky metallic

**Calculated coverage \*:** 6-8 sqm./liter (in one coat)

**Recommended dilution:** Ready to use – do not dilute

**Drying times:** Touch \*\*: 2 hours | Recoat: 2 hours | Final: 24 hours

**Shelf life:** 24 months

Package size	Quantity per pallet
3 liters	160

---

**Surface Preparation and System Recommendation:** Remove any old, loose and peeling paint. Clean the wall from dirt and dust. Apply one coat of acrylic paint from Supercryl series tinted in a similar shade to the chosen Cashmere shade. If the surface is painted with lime paint, then apply one coat of Bonderol Super before applying the acrylic paint. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

**Application:** Stir the paint well before application and while painting. It is recommended to apply first on a small area and then choose the preferred texture/method.

### To obtain an elegant Cashmere look:

Dip a brush (3" – 4" wide) in the paint container. Apply a generous quantity of the paint on the wall in wide crisscross movements. After covering a defined area, go over it with a soft plastic spatula or rounded ends stainless steel spatula, using long left-to-right movements or rotating movements to obtain smooth areas with different degrees of reflections. The different shades give the sheen and appearance of Cashmere fabric. For a rich look, use the spatula very lightly, without pressure. It is recommended to apply over a diagonal section of about 0.5-1 sqm. at a time, and ensure complete coverage. It is recommended to step away from the wall occasionally during the application, to view the entire wall. If a light shade was chosen, apply another coat of Cashmere after drying. Watch out for areas with excessive amount of paint. If it tends to run, continue to spread the paint.

**To obtain a smooth and uniform look:**

Dilute with 5%-15% of water, for easy application with the roller. Apply 2-3 coats with a short-haired roller, with uniform movements and light finishing touch, to ensure that no roller marks remain. Watch out for areas with excessive amount of paint. If it tends to run, continue to spread the paint.

**To obtain a wild, silky look:**

Use seaweed sponge or an imitation chamois cloth. Dip into a little amount of Cashmere paint and dab on the wall at intervals, so that the undercoat Supercryl is partially exposed, giving different shades and gloss. It is possible to apply two coats of Cashmere using sponge in light rotating movements. If a light shade was chosen, apply another coat of Cashmere after drying. Watch out for areas with excessive amount of paint. If it tends to run, continue to spread the paint.

**Notice:** Do not accelerate drying with a ventilator or a heat blower, to prevent splintering and cracks. The final shade and look is affected by the direct lighting on the wall and by the reflection of the light on the wall. It is possible to apply another coat after a complete drying of the first coat.

**Cleanup and Storage:** Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

**Cautions:** The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

**General Notes:** Do not apply when the wall is wet or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

\* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

\*\* At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.