

Bonding primer for reinforcing the surface to be painted.  
Interior use only.



**Product Features:** This paint provides an excellent penetration and adhesion to the surface. Fast drying, free of lead and chromates.

**Recommended Uses:** Bonding primer to reinforce various interior surfaces prior to application of acrylic topcoat paint, synthetic lime coat paint or readymade joint compound.

### Technical Data:

Product code (SKU): 710-100

Color: Transparent yellowish

Gloss: Matt

Calculated coverage \*:8-10 sqm./liter (In one coat)

Recommended dilution: Not required

Drying times: Touch \*\*: 1 hour | Final: 2 hours

Shelf life: 24 months

Package size	Quantity per pallet
18 liters	36
5 liters	100
1 liters	576

**Surface Preparation and System Recommendation:** Clean off dust, sand, grease and any other foreign substances. Remove any loose, flakey, peeling lime or excessively thick layers. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

**Application:** Stir the paint well before application and while painting.  
Apply using a brush/ Roller/ Regular airless or Airless spray. Apply one thin coat of Bonderol Super.

**Cleanup and Storage:** Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 35°C.

**Cautions:** The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

**General Notes:** Do not apply when the wall is wet or when rain is expected and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

\* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

\*\* At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.