

Quality American joint compound for filling and smoothen of gypsum board, concrete and plaster walls.

For internal use before application of paint.



Product Features: Easy to apply, easy sanding, maximal filling capacity, fast drying, certified eco-friendly.

Recommended Uses: Multi-purpose joint compound for smoothen gypsum board, concrete and plastered walls. Designed for grout infrastructure, cement and mineral infrastructures including gypsum boards. In bathrooms it is recommended to apply Super Fine joint compound.

Technical Data:

Product code (SKU): 725-045

Color: Off-white

Gloss: Matt

Calculated coverage *: 1-2 Kg /sqm. (In one coat)

Recommended dilution: Paint is ready for use

Drying times: Touch **: 2 hours | Recoat: 4 hours | Final drying: 24 hours.

Shelf life: 24 months

Package size	Quantity per pallet
4.5 Kg	100
25 Kg	36

Surface preparation and system recommendation: Clean the surface to be painted from dust, oil and all other dirt, make sure that the surface is completely dry. Remove any loose and peeling paint, Sand with sandpaper and clean off dust.

New unpainted interior walls with interior plastering:

If the final finishing of the wall is designed to be an acrylic topcoat (Supercryl series etc.), one coat of Bonderol Super Primer should be applied after the application of Magic Bond Super. If the final finishing is lime topcoat it can be applied directly on Magic Bond Super. Make sure that the surface was prepared in accordance with IS 1920.

Application: The product is ready to use without the need for further dilution. Stir the paint before application. Smooth the wall with the joint compound using a spatula, with one layer up to three thin layers as needed. Make sure that the total thickness of all layers does not exceed 1.5 mm. Allow drying and sand the wall using fine sandpaper. The product can be applied using an Airless spray.

Cleanup and storage: Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 35°C.

Cautions: The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS). Not recommended for use in bathrooms.

General notes: Do not apply when the wall is wet and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.