

Synthetic Powder putty. designed to fill holes and seal fine cracks.  
For interior use only.



**Product Features:** Excellent filler, does not shrink upon drying, easily sanded.

**Recommended Uses:** Fills and seals holes and fine cracks in interior concrete, plaster and other walls.

### Technical Data:

Product code (SKU): 771-002

Color: Off-white

Gloss: Matt

Recommended dilution: Water (see recommendation in surface preparation section)

Drying times: Touch \*\*: 1 hour | Recoat: 1 hours | Final: 24 hours

Shelf life: 24 months

Package size	Quantity per pallet
1 Kg	1008
5 Kg	240

### Surface Preparation and System Recommendation:

**Interior Whitewashed Surfaces:** Remove dust, dirt and any other foreign matter. Pour water into a clean container. Scatter Kalcimo X uniformly into the water at a ratio of 2 parts powder for each part of water. Wait for about one minute before stirring, to prevent lumps. Stir for about one minute in the same direction. A ready to use paste is obtained.

**Application:** The paste is workable for 90-120 minutes after its preparation. Fill the holes and the cracks with Kalcimo X using a spatula. Once the repaired surface is dry, sand it with sandpaper. If the paint to be painted on the wall is acrylic paint, then apply one coat of Bonderol Super on the repaired areas before the application.

**Cleanup and Storage:** Clean work tools with soap and water immediately after use. Store in a roofed and ventilated place, below 35°C.

**Cautions:** The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

**General Notes:** Do not apply when the wall is wet or when rain is expected and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

\* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

\*\* At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.