

High quality, water based acrylic paint.
Especially designed for exterior walls.
In accordance with IS 1945 and certified eco-friendly.



Product Features: Provides complete protection against extreme climate conditions, long term retention of color and good wall appearance. Excellent adhesion to the surface, resists concrete salts damages, breathing paint, free of lead and chromates. Contains pure acrylic emulsion.

Recommended Uses: Exterior concrete and bricks walls.

Technical Data:

Product code (SKU): 736-80X

Color: White and over 2500 colors from Tambour fan decks

Gloss: Matt

Calculated coverage *: 11-12 sqm./liter (In two coats) depends on surface absorption

Recommended dilution: Water (see recommendation in "Application" section)

Drying times: Touch **: 1 hour | Recoat: 2-3 hours | Cleaning and washing: 72 hours

Shelf life: 24 months

Package size	Quantity per pallet
18 liters	36
5 liters	100
1 liters	576

Surface Preparation and System Recommendation:

New Concrete and Cement Plaster Surfaces:

Paint can be applied only after the plaster is completely cured (about one month post application). Remove any old, loose and peeling paint. Remove dust and apply one coat of Exterior Bonding Primer diluted with 30% of Tambour Mineral White Spirit. Allow drying for at least 24 hours. Apply two coats of Supercryl MD. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

Painted Interior Walls:

Remove any old, loose and peeling paint. Remove dust and use Exterior Acrylic Putty to fill holes and smooth the surface. Allow hard drying and sand with sandpaper to a smooth surface. Apply 2 coats of Supercryl MD. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

Application: Stir the paint well before and during application.

Apply using a brush/ Roller/ Airless: Dilute the paint with water. For the first coat by 15% - 20% and stir well, for an additional coat by 10%-15%.

Cleanup and Storage: Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

Cautions: The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

General Notes: Do not apply when the wall is wet or when rain is expected and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.