



A water based white primer based on acrylic resins.
Ensures excellent adhesion of the acrylic topcoat to the surface.
Exterior and interior use.

Product Features: Fine roughness primer that promotes adhesion on new surfaces. Can be used also as a primer underneath Tambour Special Effects.

Recommended Uses: Exterior surfaces such as: concrete, cement, plasterwork and existing coats of paints. Suitable as a primer for Flexible Acrylic Shlicht or new surfaces.

Technical Data:

Product code (SKU): 738-501

Color: 1650 Colors from Tambour fan deck

Gloss: Matt

Calculated coverage *: 12 sqm./liter (In one coat)

Recommended dilution: Water (see recommendation in "Application" section)

Drying times: Touch **: 1 hour | Recoat: 2 hours | Final: 24 hours

Shelf life: 24 months

Package size	Quantity per pallet
18 liters	36
5 liters	100
1 liter	576

Surface Preparation and System Recommendation:

Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2. Remove any old, loose and peeling paint. Clean the wall with a water jet in a pressure of 120atm. Repair the wall as needed (for new concrete, paint can be applied only after the concrete is completely cured, about one month after the application).

Before application, detach all scaffolding joints, wires and planks from the wall and anchor the scaffold according to standard requirements.

Application:

Apply using brush /roller: Apply one coat of Exterior Bonding Primer diluted by water up to 25%. Allow drying for 4-6 hours and then apply Acrylic Shlicht or any other acrylic paint such as: Supercryl MD and Supercryl MD 45 (as described in application instructions).

Cleanup and Storage: Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 35°C.

Cautions: The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

General Notes: Do not apply when the wall is wet or when rain is expected for about 72 hours before or after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.