

Solvent based bonding primer, especially designed for exterior walls. Ensures excellent adhesion of the acrylic topcoat to the surface.



Product Features: excellent penetration and adhesion to the wall which provides long-term resistance to alkaline materials. Free of lead and chromates.

Recommended Uses: Painting exterior walls. Suitable as a primer for: Tambourflex Paint System, Flexible Acrylic Shlicht, Supercryl MD, Supercryl and Supercryl MD 45. also suitable to use as a stain blocker and to rapier fire damages.

Technical Data:

Product code (SKU): 737-000

Color: White (Underneath Shlicht it is recommended to tint the primer in a similar color as the Acrylic Shlicht)

Gloss: Matt

Calculated coverage *: 11-12 sqm./liter (In two coats) for White or tinted

Recommended dilution: Up to 30% of Tambour Mineral White Spirit

Drying times: Touch **: 1 hour | Recoat: 4 hours | Final: 24 hours

Shelf life: 24 months

Package size	Quantity per pallet
18 liters	27
5 liters	100

Surface Preparation and System Recommendation: Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2. Remove any old, loose and peeling paint. Clean the wall with a water jet in a pressure of 120atm. Repair any concrete and plaster defects as needed (for new concrete, paint can be applied only after the concrete is completely cured, about one month after the application). Apply Tambourflex Bonding Primer using a brush or roller. Allow drying for 4 hours before applying Tambourflex Paint System or any other topcoat. Do not apply the Tambourflex Bonding Primer and leave it uncoated for more than a week.

Application: Stir the paint well before application to obtain a uniform mixture.

Roller/ Spray (Airless) Application: Dilute the primer with up to 30% of Tambour Mineral White Spirit.

Cleanup and Storage: Clean work tools with Tambour Mineral White Spirit immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

Cautions: Flammable. This product is poisonous for water creatures and could cause a long-term damage to the water. Also could harm infants.

Do not inhale, avoid contact with the skin. In a case of fire, use the Fire Fighting Foam. In case of accident get medical attention. Use the right container to prevent environmental pollution.

Use gloves, protective glasses and ABEK P3 type mask.

General Notes: Do not apply when the wall is wet or when rain is expected for about 72 hours before or after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.