

# Flexible Decorative Acrylic Plaster ("Shlicht") TM 40 Fine

# Tambour

Acrylic Shlicht - Flexible Acrylic Plaster coating.  
Decorative flexible system for painting exterior and interior walls.  
Provides an authentic look, with fine scratches.



**Product Features:** Easy to apply, provides excellent protection against effects of extreme weather conditions, and also against mould and bacteria. Provides excellent cracks bridging properties and great adhesion to the surface. Maintains the wall's color and look for extended periods. Contains durable pigments for outdoor conditions. Breathable, free of lead and chromates. In accordance with IS 1731 (cracks bridging properties up to 1 mm).

**Recommended Uses:** Interior and exterior surfaces such as: concrete, brick, cement, plasterwork, existing coats of paints, gypsum boards.

## Technical Data:

**Product code (SKU):** 738-XXX (738-670 Base W, 738-671 Base WW, 738-672 Transparent Base)

**Color:** Colors from Tambour fan deck (shake at least 5 minutes)

**Gloss:** Matt

**Texture:** Fine 40

**Calculated coverage \*:** 2-2.6 kg/sqm.

**Drying times:** Touch \*\*: 2-3. Hours (workability: about 20 minutes) | Final: 72 hours

**Shelf life:** 24 months

Package size	Quantity per pallet
24 Kg	36

**Surface Preparation and System Recommendation:** Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2. Remove any old, loose and peeling paint. Clean the wall with a water jet in a pressure of 120atm. Repair the wall as needed (for new concrete, paint can be applied only after the concrete is completely cured, about one month after the application).

Before application, detach all scaffolding joints, wires and planks from the wall and anchor the scaffold according to standard requirements. Before application stir the paint at low speed using a mechanical mixer.

## Application:

**Black plaster:** Apply using a brush or roller one coat of Primer For Shlicht (catalog No. 738-500) or Exterior Bonding Primer (catalog No. 738-501) or Tambourflex Primer Solvent Based (catalog No. 737-000). Apply the primer according to the manufacturer's instructions. Allow drying to a hard coat.

**Painted Interior Walls:** If the surface to be painted is porous or weak, apply one coat of Tambourflex Primer Solvent Based (catalog No. 737-000) after the surface preparation. If the surface is intact apply one coat of Primer For Shlicht (catalog No. 738-500) or Exterior Bonding Primer (catalog No. 738-501). Allow drying to a hard coat.

[www.tambourpaints.com](http://www.tambourpaints.com)

**Flexible Decorative Acrylic Plaster ("Shlicht") Application:** Apply on coat of Shlicht using a metal spatula. Remove excess Shlicht by holding the spatula in an angle to the wall. After a short time, go over the applied surface in rotating movements using a plastic spatula, until the required texture is obtained (to obtain a rough texture, go over the applied surface with a moist sponge pad). Apply the shlicht consecutively and constantly through the entire wall to obtain a uniform shade.

**Textures:** (Apply first on a small area and then choose the preferred method)

**A common application:** Rotating movements using a spatula.

**Application for one floor house (up to 4 meters):** Horizontal movements using a plastic spatula.

**Application for a house with two floors or more (above 4 meters):** Vertical movements using a plastic spatula.

**Cleanup and Storage:** Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

**Cautions:** The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

**General Notes:** Do not apply when the wall is wet or when rain is expected for about 72 hours before or after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

\* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

\*\* At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.