

Synthetic lime paint for maximal coverage.  
Designed especially for interior walls and ceilings in new constructions.  
In accordance with IS 1637 and certified eco-friendly.



**Product Features:** This paint provides excellent coverage, chalking resistant free of lead and chromates.

**Recommended Uses:** Especially designed for painting interior walls and ceilings in new constructions and interior plastered and concrete walls.

### Technical Data:

Product code (SKU): 731-600

Color: White

Gloss: Matt

Calculated coverage \*: 8-9 sqm./liter (In two coats)

Recommended dilution: Water (see recommendation in "Application" section)

Drying times: Touch \*\*: 1 hour | Recoat: 2 hours | Final: 24 hours

Shelf life: 24 months

Package size	Quantity per pallet
18 liters	36
16 liters	36

### Surface Preparation and System Recommendation:

**New, Unpainted, Plastered Interior Walls:** Smooth the surface using sandpaper. Remove dust and fill holes with Calcimo X. Apply 2-3 coats of Gmar Sid Super. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

**Interior Whitewashed Surfaces:** Remove any loose, flakey, peeling lime. Sand with sandpaper to a smooth surface. Remove dust and fill holes with Calcimo X. Apply two coats of Gmar Sid Super. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

**New Plastered Walls:** Apply first coat of Yad Rishona (a water based primer and first coat for filling and coverage of new construction), and then apply second coat of Gmar Sid Super diluted by 15% - 20% of water, or, apply two coats of Gmar Sid Super diluted by 15% - 20% of water.

**Application:** Stir the paint well before application and while painting. This paint should not be tinted.

**Apply using a brush/ Roller:** Dilute the paint with water for the first coat by 15% - 20%. Dilute the paint with water for an additional coat by up to 20%.

**Apply using Airless:** Dilute the paint with up to 30% of water.

**Cleanup and Storage:** Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

**Cautions:** The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only.

Specific information regarding the product is available in the safety manual (MSDS).

**General Notes:** Do not apply when the wall is wet or when rain is expected and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Do not wash the walls. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

\* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

\*\* At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.