

A water based primer and first coat for filling and covering walls in new construction. Interior use only.



Product Features: Excellent filling capacity, especially for leveling plaster and new cement. Creates a smooth surface that is suitable for additional applications of paint. Free of lead and chromates.

Recommended Uses: Filling, leveling and covering plastered walls in new construction and gypsum walls.

Technical Data:

Product code (SKU): 731-500

Color: White

Gloss: Matt

Calculated coverage *: 7 sqm./liter (In one coat)

Recommended dilution: Water (see recommendation in "Application" section)

Drying times: Touch **: 1 hour | Recoat: 2 hours | Final: 7 days

Shelf life: 24 months

Package size	Quantity per pallet
18 liters	36

Surface preparation and system recommendation:

Interior Plastered and New Cement Walls and Ceilings:

Sand the wall with sandpaper to a smooth surface. Remove dust and fill holes with Calcimo X. Apply 2-3 coats of Yad Rishona, depends on the surface type. It is recommended to smooth the surface with sandpaper between the coats and after the final coat of Yad rishona is applied. Apply 2-3 coat of Gmar Sid Super or Polisid or any other recommended Tambour topcoat paint. If the topcoat is an acrylic paint, apply one coat of Bonderol Super after applying Yad Rishona. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

Application: Stir the paint well before application and while painting.

Apply using a brush/ Roller: Dilute the paint with water by 15% - 20%.

Apply using an Airless: Dilute the paint with water by up to 30%.

Cleanup and storage: Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and well ventilated place, below 35°C.

Cautions: The paint is inedible; the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

General notes: Do not apply when the wall is wet or when rain is expected for about 72 hours before and after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.