

Water based acrylic paint, especially designed for gypsum boards.
Interior use only.
In accordance with IS 809 and certified eco-friendly.



Product Features: Provides a great adhesion to gypsum boards and plastered walls. With exceptional coverage and washability, extra white color, breathing paint, free of lead and chromates.

Recommended Uses: Interior plaster (gypsum) walls.

Technical Data:

Product code (SKU): 735-100 White, 735-202 Base P

Color: White and colors according Tambour fan decks (for base P)

Gloss: Matt

Calculated coverage *: 10-11 sqm./liter (In two coats)

Recommended dilution: Water (see recommendation in application section)

Drying times: Touch **: 1 hour | Recoat: 2 hours | Cleaning and washing: 72 hours

Shelf life: 24 months

Package size	Quantity per pallet
16 liters	36

Surface Preparation and System Recommendation:

Interior Whitewashed Surfaces: Remove any loose, flakey, peeling lime or excessively thick layers. Sand with sandpaper to a smooth surface. Clean off dust thoroughly. If needed, fill holes with Calcimo X. Apply one coat of Bonderol Super Primer. Allow drying to a hard coat and apply two coats of Multicryl.

Painted Interior Walls: Remove any old, loose and peeling paint. Apply one coat of Bonderol Super Primer on the peeling paint areas. Smooth the surface using readymade joint compound – Magic Bond Super (for interior applications only) or Glue Putty 2000, and apply one coat of Bonderol Super Primer on it. Allow drying to a hard coat. Apply two coats of Multicryl. When the old paint coat is intact and cannot be removed, apply two coats of Multicryl.

New, Unpainted, Plastered Interior Walls: Smooth the surface lightly using sandpaper. Remove dust and fill holes with Calcimo X. To obtain a smooth surface, apply one coat of Tambourfill diluted by 20%-30% of water and allow drying to a hard coat. Apply two coats of Multicryl.

New Plastered Walls: Apply 2-3 coats of Multicryl. In a case the wall was repaired with readymade joint compound, apply one coat of Bonderol Super Primer on the repaired areas, before applying Multicryl.

Application: Stir the paint well before application and while painting.

Apply using a brush/ Roller/ Airless: Dilute the paint with water for the first coat by 15% - 20% and stir well. Dilute the paint with water for an additional coat by 10%-15%. Apply 2-3 coats, according to the surface type.

Cleanup and Storage: Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

Cautions: The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

General Notes: Do not apply when the wall is wet or when rain is expected and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.