

Water based synthetic lime paint. Provides a smooth look.  
Designed especially for interior walls and ceilings.  
In accordance with IS 1637 and certified eco-friendly.



**Product Features:** Provides a great adhesion to the surface and an excellent coverage. Extra white color, free of lead and chromates. Interior use only.

**Recommended Uses:** Especially designed for painting interior walls and ceilings.

### Technical Data:

Product code (SKU): 731-700

Color: White

Gloss: Matt

Calculated coverage \*: 8-9 sqm./liter (In two coats)

Recommended dilution: Water (see recommendation in "Surface preparation" section)

Drying times: Touch \*\*: 1 hour | Recoat: 2 hours | Final: 24 hours

Shelf life: 24 months

Package size	Quantity per pallet
18 liters	36
5 liters	80
2.5 liters	160

### Surface Preparation and System Recommendation:

**Interior Whitewashed or Painted Surfaces:** Remove any loose, flakey, peeling lime. Sand with sandpaper to a smooth surface. Remove dust and apply first coat of Polisid diluted by 15% - 20% of water. Apply second and third coats of Polisid diluted by 10% - 15% of water. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

**New, Unpainted, Plastered Interior Walls:** Smooth the surface using sandpaper. Remove dust and apply one coat of Tambourfill (walls filling primer) or Yad Rishona (a water based primer with good filling properties). Allow drying and apply 2-3 coats of Polisid diluted with 15-20% of water. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

**Application:** Stir the paint well before application and while painting.

**Apply using a Roller:** To obtain a uniform finish, apply the paint until complete coverage is received.

**Cleanup and Storage:** Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

**Cautions:** The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only.

Specific information regarding the product is available in the safety manual (MSDS).

**General Notes:** Do not apply when the wall is wet or when rain is expected and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Do not wash the walls. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

\* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

\*\* At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.