

Plastic, water based economy paint for interior walls.



**Product Features:** Excellent adhesion to the surface, breathing paint. Good coverage, free of lead and chromates.

**Recommended Uses:** Painting interior plastered and gypsum walls, bricks and concrete walls.

#### Technical Data:

Product code (SKU): 731-800

Color: White

Gloss: Matt

Calculated coverage \*:9-10 sqm./liter (In one coat)

Recommended dilution: Water (see recommendation in "Application" section)

Drying times: Touch \*\*: 1 hour | Recoat: 2 hours | Final: 24 hours

Shelf life: 24 months

Package size	Quantity per pallet
18 liters	36
5 liters	80

#### Surface preparation and system recommendation:

**Interior Whitewashed surfaces:** Remove any loose, flakey, peeling lime or excessively thick layers. Sand with sandpaper to a smooth surface. Clean off dust thoroughly. Fill holes with Calcimo X. Apply one coat of Bonderol Super Primer. Allow drying to a hard coat, and then apply two coats of Plastikir. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

**Painted Interior Walls:** Remove any old, loose and peeling paint. Apply one coat of Bonderol Super Primer on the peeling paint areas. Smooth the surface using readymade joint compound – Magic Bond Super (for interior applications only), and apply one coat of Bonderol Super Primer on it. Allow drying to a hard coat. Apply two coats of Plastikir. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

**New, Unpainted, Plastered Interior Walls:** Smooth the surface lightly using sandpaper. Remove dust and fill holes with Calcimo X, and apply one coat of Tambourfill to receive a smooth wall. Allow drying to a hard coat. Apply two coats of Plastikir. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

**Gypsum Walls:** Clean off dust and then apply 2-3 coats of Plastikir, diluted by 10%-15% of water

**Application:** Stir the paint well before application and while painting.

**Apply using a brush/ Roller/Airless:** Dilute the paint with water for the first coat by 15% - 20% and stir well. Dilute the paint with water for an additional coat by 10%-15%. Apply 2-3 coats, according to the surface type.

**Cleanup and storage:** Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and well ventilated place, below 35°C.

**Cautions:** The paint is inedible; the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

**General notes:** Do not apply when the wall is wet or when rain is expected for about 72 hours before and after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

\* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

\*\* At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.