

Synthetic glossy clear wood varnish.
For Interior and exterior use.



Product Features: Developed especially to resist extreme climate conditions. The wood varnish is designed to protect wood surfaces and maintain the high gloss and the natural texture of the wood.

Recommended Uses: Recommended for application on interior and exterior wooden surfaces, such as decorative items, garden furniture, roof frames, wooden fences, doors, door frames, etc.

Technical Data:

Product code (SKU):	149-001
Color:	Transparent
Gloss:	Glossy
Calculated coverage *:	10 sqm./liter (in one coat)
Recommended dilution	Tambour Mineral White Spirit/1-32 thinner (see recommendation in "Application" section)
Drying times:	Touch **: 4 hour Recoat: 24 hours Final: 24 hours
Shelf life:	24 months

Package size	Quantity per pallet
0.75 liter	640
4.5 liter	100

Surface preparation and system recommendation:

New, Unpainted Wood:

Remove any dust, dirt and grease stains. Ascertain that the surface is dry. Sand with sandpaper 0 or 360 and clean off sanding dust. Apply a first coat of Exterior Synthetic Wood Varnish No. 8. Allow drying to a hard coat. Sand again with sandpaper 0 or 360 and clean off sanding dust. Apply another coat (until a glossy finish is obtained). Ascertain complete drying between coats.

Old, Painted Wood:

Remove any old, loose and peeling coats and paint residue. Clean off dirt and dust. Ascertain that the surface is dry. Sand with sandpaper 0 or 360 and clean off sanding dust. Apply a first coat of Exterior Synthetic Wood Varnish No. 8. Allow drying to a hard coat. Sand again with sandpaper 0 or 360 and clean off sanding dust. Apply another coat (until a glossy finish is obtained). Ascertain complete drying between coats.

Notice: To obtain high durability and maximum protection from UV radiation, apply the Exterior Synthetic Wood Varnish No. 8 over Water Based tinted Varnit. Darker colors provide better protection. For exterior application, apply at least three coats.

Application: A ready to use wood Varnish. Stir well before application and while painting.

When needed, thin with Tambour Mineral White Spirit by 5%-10%.

Brush Application: Apply along the wood grain.

Airless Application: Dilute with 1-32 thinner.

Cleanup and storage: Clean work tools with Tambour Mineral White Spirit immediately after use. Pour a thin layer of mineral white spirit on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and well ventilated place.

Cautions: The paint is inedible; any work that includes application and use of this product shall be performed according to the applicable Safety, Health and Environmental regulations. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS). Avoid inhaling the paint or its vapors.

General notes: Do not apply when the wall is wet and/or rain is expected for about 72 hours before or after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.