

Water based tinted paint sample for all shades of the Tambour fan decks.
Designed only to demonstrate the chosen shade.
For interior use only.



Recommended Uses: Interior plaster, concrete and bricks walls and ceilings.

Technical Data:

Product code (SKU): 732-6XX

Color: Shades from Tambour fan decks

Gloss: Matt

Calculated coverage *: 2 sqm./ 0.25 liter

Recommended dilution: Water (see recommendation in application section)

Drying times: Touch **: 1 hour | Final: 12 hours (until the final shade is obtained)

Shelf life: 24 months

Package size	Quantity per pallet
0.25 liters	

Surface Preparation and System Recommendation:

Interior Whitewashed Surfaces:

Choose a place on the wall where the paint can't be removed. Apply 1-2 coats of Tinted Sample using a brush. For darker shades it may require an additional coat to obtain the exact color. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

Application: Stir the paint well before application and while painting.

Dilute the paint with water by 15% - 20% and stir well. Apply using a brush. The obtained shade can vary, depending on the surface, the application mode and the light. Therefore there could be a difference between the chosen shade and the obtained shade.

Cleanup and Storage: Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

Cautions: The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

General Notes: Do not apply when the wall is wet or when rain is expected and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.