



Aerosol Paint, available in various shades and effects.
For interior and exterior use.

Product Features: Fast drying. Easy application. For interior and exterior use. Free of lead.

Recommended Uses: Interior and exterior wooden, metal, plaster and concrete surfaces.

Technical Data:

Product code (SKU): 465-XXX

Types: Smooth

Gloss: Glossy and Matt (depends on the shade)

Drying times: Touch **: 10 minutes | Recoat: 1 hour | Final: 1 hour

Shelf life: 24 months

Package size	Quantity per pallet
400 ml/ 235 gr	12 carton packages

Surface preparation and system recommendation:

Before application, make sure that the surface to be painted is clean and dry. Remove rust, dirt, grease and any other foreign matter. It is recommended to cover the area around the painted place.

Application: Ready to use aerosol paint. Shake thoroughly before application for at least one minute. Apply thin coats of the paint from a distance of 25 cm. if needed, recoat after an hour.

Cleanup and storage: Clean work tools with White Spirit, immediately after use. Store in a roofed and ventilated place below 30°C. After use turn the spray upside down and press the button for five seconds or until no more paint comes out to prevent the spray from plugging.

Cautions: Any work that includes application and use of this product shall be performed according to the applicable Safety, Health and Environmental regulations. The paint is inedible, extremely flammable, keep out of reach of children. Avoid contact with skin and eyes. Use in a well ventilated area only. Avoid inhaling the lacquer or its vapors. Specific information regarding the product is available in the safety manual (MSDS). Wash your hands with water and soap after completing application. Keep away from direct sun radiation. Don't expose the container to a temperature above 50°C. Flammable content is 85%.

General notes: Do not apply when the wall is wet or when rain is expected for about 72 hours before and after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and

that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.