

Unique acrylic paint, for painting wood, metal and walls, in matt, satin and high gloss.



Product Features: Odorless, acrylic paint with a unique elegant finish. Washable for easy cleaning. Highly durable. Easy application. Fast drying. Free of lead and chromates. Ready to use product.

Recommended Uses: Interior and exterior wooden surfaces, such as pergolas, garden furniture, roof frames, wooden fences, doors and door frames.

Technical Data:

Product code (SKU):	785-XXX Matt, 787-XXX Satin, 784-XXX Glossy.
Color:	White and 1200 colors from Tambour fan deck (784-XXX, white & pastel bases)
Gloss:	Matt, Satin, glossy
Calculated coverage *:	10 sqm./liter (in one coat)
Recommended dilution	Water (see recommendation in "Application" section)
Drying times:	Touch **: 1 hour Recoat: 2 hours Final: 24 hours
Shelf life:	24 months

Package size	Quantity per pallet
0.25 liter	1440
0.75 liter	576
2.5 liters	210
4.5 liters	100
18 liters	27

Surface preparation and system recommendation:

New, Unpainted Wood:

Before the application, make sure that the wood is dry. Smooth the surface with sandpaper and remove dust. Apply 2-3 coats of Water Based Poliur

Painted wood:

Remove old paint, using sandpaper. Clean thoroughly. Fill holes with PVA Putty and allow drying completely. Sand the putty to obtain a uniform, clean and smooth surface. Apply 2-3 coats of Water based Poliur.

Unpainted metal and/or painted metal in poor condition:

Remove rust, flaking metal and any other foreign matter with a steel brush and sandpaper and then rinse with water. Apply two coats of Multi-Purpose Water Based Primer and allow drying to a hard coat. Apply two coats of Poliur Water Based. Where rust cannot be removed by the aforementioned mechanical means, treat the rust with Tambour Rust Converter and then apply two coats of Multi-Purpose Primer, diluted with water and allow drying to a hard coat.

Galvanized Steel and Formica:

Sand the surface lightly to remove grayness of the galvanized steel and to abrade the surface. Remove all dirt, dust and fat, using water and then rinse thoroughly. Apply 1-2 coats of Multi-Purpose Primer, diluted with water and allow drying to a hard coat. Apply two coats of Water Based Poliur.

Interior, whitewashed & painted surfaces:

Remove loose, peeling or thick coats of whitewash. Sand until the surface is smooth. Remove dust thoroughly. Apply one coat of Bonderol Super primer and allow drying for 4 hours. Apply two coats of Water Based Poliur, where the first coat is diluted with about 10 -15% water. Allow to dry for 3 hours and apply a

second coat diluted with about 10-15% water.

New Interior Walls (Plaster):

Smooth the surface lightly using sandpaper. Remove dust and fill holes with synthetic powder Calcimo X. Apply 1-2 coats of Tambourfil diluted with 5-10% water and allow drying for 4 hours. Apply 2 coats of Water Based Poliur, where the first coat is diluted with about 10 -15% water. Allow to dry for 3 hours and apply a second coat diluted with about 10-15% water.

Smooth surface of interior walls:

Use Glue Putty 2000 or Joint Compound to smooth the wall. Strictly ensure that the putty is applied in a smooth, uniform coat. Allow to dry completely (you may wait up to 24 hours, depending on the coat thickness). Apply one coat of Bonderol Super primer and allow drying for 4 hours.

Apply two coats of Water Based Poliur, diluted with about 10-15% water, allowing 3 hours to dry between coats. Use a short haired roller, intended for semi-glossy paints or a pad to apply Water Based Poliur.

Application: Mix thoroughly before application and occasionally during application.

Ready to use paint when applied with a brush.

When applied with a roller, dilute with about 5-10% water.

Air spraying, dilute with 20-30%.

Cleanup and storage: Clean tools and work site with soap and water after application is completed.

Pour a thin layer of water on the remaining paint and close the container tightly, to prevent air penetration. Store in a roofed, ventilated place.

Cautions: Inedible, keep away from fire and out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

General notes: Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.