

Water based acrylic transparent wood stain.

Designed to protect wooden surfaces and maintain the natural texture of the wood.
Interior and exterior use.



Product Features: Especially designed to maintain the natural look of the wood and to protect it from moisture penetration. Contains active agents to prevent mould development. Fast drying. Easy to apply. Free of lead and chromates and therefore suitable to use on children's furniture and toys. Certified eco-friendly.

Recommended Uses: Recommended for application on interior and exterior wooden surfaces such as: pergolas, children's furniture and toys, garden furniture, roof frames, wooden fences, doors and door frames.

Technical Data:

Product code (SKU): 786-000

Color: Transparent

Gloss: Matt

Calculated coverage *: New, unpainted wood: 9 sqm./liter (in one coat)
Painted wood: 12 sqm./liter (in one coat)

Recommended dilution: Ready to use

Drying times: Touch **: 1 hour | Recoat: 2-3 hours | Final: 24 hours

Shelf life: 24 months

Package size	Quantity per pallet
0.75 liter	576

Surface preparation and system recommendation:

Notice: application of the transparent Water Based Varnit alone does not provide full protection from UV radiation. It is recommended to apply first Water Based Varnit Wood Stain – Satin. Do not apply the wood stain over wet wood.

New, Unpainted Wood / Painted Wood:

Sand the wood using sandpaper 0 or 360. Remove any old, loose and peeling coats and paint residue. Clean off dirt, dust and grease. Apply transparent Water Based Varnit Wood Stain.

Application: A ready to use product. Stir the wood stain well before application and while painting.

Soft Brush Application: Apply along the wood grain. Apply several coats until full coverage is achieved. The wood stain appears to have a milky white color in its can, but turns clear once it is dry.

Cleanup and storage: Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and well ventilated place, below 35°C.

Cautions: The paint is inedible; the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

General notes: Do not apply when the wall is wet and/or rain is expected for about 72 hours before or after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.