

Water based acrylic wood stain designed to protect wooden surfaces.



Product Features: Especially developed to resist extreme climate and moisture conditions. Protects against moisture penetration and contains active agents to prevent mould development. The wood stain is designed to protect wood surfaces and maintain the natural texture of the wood. Fast drying. Easy to apply. Free of lead and chromates. Certified eco-friendly.

Recommended Uses: Recommended for application on interior and exterior wooden surfaces, such as pergolas, garden furniture, roof frames, wooden fences, doors and door frames.

Technical Data:

Product code (SKU): 781-XXX

Color: Transparent and 33 machine tinted colors from given collection

Gloss: Satin

Calculated coverage *: New, unpainted wood: 15-18 sqm./liter (in one coat)
Painted wood: 20-23 sqm./liter (in one coat)

Recommended dilution: Water (see recommendation in "Application" section)

Drying times: Touch **: 1 hour | Recoat: 2-3 hours | Final: 24 hours

Shelf life: 24 months

Package size	Quantity per pallet
0.75 liter	576
4.5 liters	100
18 liters	36

Surface preparation and system recommendation:

Notice: It is recommended to apply the wood stain first on a small area since that the final shade obtains depends on the natural shade and type of the wood, dilution percent and application.

New, Unpainted Wood:

Remove any dust, dirt and grease stains using Tambour Mineral White Spirit. Sand with sandpaper 0 or 360 and clean off sanding dust. Apply the first coat of Varnit for Wood diluted with about 25% of water to achieve good absorption and adhesion to the wood. Allow drying to a hard coat. Apply another two coats without dilution (until a satin finish is obtained). Ascertain complete drying between coats (two hours

between coats). Sand with sandpaper 0 or 360 between the coats. Do not sand after applying the last coat. To obtain high durability and protection, apply one coat of Transparent Water Based Varnit wood stain. In a case that the desirable shade is obtained after less than three coats, to complete the system apply one coat of Transparent Water Based Varnit wood stain.

Old, Wood stain Painted Wood:

Remove any old, loose and peeling coats and paint residue. Clean off dirt and dust. Continue as instructed above.

Application: A ready to use wood stain. Stir the wood stain well before application and while painting.

Brush/ sponge/roller Application: Apply along the wood grain. Apply several coats until a satin gloss is obtained.

Dilute only the first coat with about 25% of water.

It is recommended to use a special sponge designed to apply wood stain.

Cleanup and storage: Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and well ventilated place, below 35°C.

Cautions: The paint is inedible; the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

General notes: Do not apply when the wall is wet and/or rain is expected and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. This product should be carefully tied down during transport.

* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

** At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.