

# Acrylic Shlicht Primer



Primer for Flexible Acrylic Plaster "Shlicht".

Exterior and interior use.



**Product Features:** Promotes adhesion of the Shlicht to a new walls.

**Recommended Uses:** Interior and exterior surfaces such as: concrete, brick, cement and plasterwork.

On a painted acrylic surfaces or in industrial or close to sea surfaces, it is recommended to apply Tambourflex Primer based on Mineral White Spirit.

## Technical Data:

Product code (SKU): 738-500

**Color:** Colors from Tambour fan deck (tint the Primer in a similar color as the Acrylic Shlicht)

**Gloss:** Matt

**Texture:** Smooth

**Calculated coverage \*:** 6-8 sqm./liter (In one coat) depends on surface absorption

**Recommended dilution:** Water (see recommendation in "Application" section)

**Drying times:** Touch \*\*: 1-2 Hours, depends on weather | Final (before Acrylic Shlicht application): 24 hours (depends on the temperature during application).

**Shelf life:** 24 months

Package size	Quantity per pallet
18 liters	36
5 liters	100

**Surface Preparation and System Recommendation:** Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2. Remove any old, loose and peeling paint. Clean the wall with a water jet in a pressure of 120atm. Repair the wall as needed (for new concrete, paint can be applied only after the concrete is completely cured, about one month after the application).

Before application, detach all scaffolding joints, wires and planks from the wall and anchor the scaffold according to standard requirements.

### **Application:**

**Apply using brush /roller:** Apply one coat of Acrylic Shlicht Primer diluted by water up to 25%. Allow drying for 4-6 hours and then apply Acrylic Shlicht.

**Cleanup and Storage:** Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

**Cautions:** The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

**General Notes:** Do not apply when the wall is wet or when rain is expected for about 72 hours before or after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion. This product should be carefully tied down during transport.

\* The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.

\*\* At 25°C and 65% humidity.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.