



Unique Antique Effect, Authentic Texture, For Interior Use.



Main Features: Creates an antique look in a variety of magnificent shades.

Applications: For decorative interior painting of concrete walls, gypsum, and suitable wooden surfaces.

Technical Specifications:

Product Code: 790-0XX

Shade: 10 shades from the colorant dispenser

Gloss: Matte

Calculated spreading rate*: 9-11 sq.m. per liter

Dilution: When applying: ready for use | Cleaning: soap and water.

Drying times:

Dry to touch: two hours | Complete drying: 48 hours

Shelf life: 24 months.

Container size	Quantity per palette
3 liters	180

Surface and paint system preparation: Thoroughly clean dust and oils and remove any loose paint. Apply the paint on a substrate painted with acrylic paint or with a quartz primer tinted with a shade close to the selected antique shade.

Method of application: Apply the **Antique** using a **brush**. Apply in short strokes in variable directions. Work on sections, 1-2 sq.m. at a time. After about 3-8 minutes (depending on the room temperature), lightly press the paint with the special spatula for the Antique or with a stainless steel plasterer's trowel. Continue to paint until the entire wall is covered, paying attention to the connections between the paint sections, to avoid conspicuous connections.

Cleaning Tools and Storage: Clean the tools with soap and water immediately after use. Close the container well to prevent air from penetrating. Store in a sheltered and well-ventilated place: below 35 °C.

Warnings and safety instructions: The material is not edible, it has not designated a hazardous substance and does not contain materials requiring any special warnings or labeling. Keep out of the reach of children. Ensure proper ventilation while applying the paint. The exact information for the product is available on the safety sheet (MSDS).

General notes: Do not paint if the wall is wet and/or if the wall temperature is below 10°C and the relative humidity is above 85%. Do not mix this material with materials that have not been recommended by us. Achieving the desired results depends on correct application of the product while observing the instructions for use. Before applying the product, the user must ensure that it is indeed intended for the planned use and that the surface to be painted and its surface have been prepared properly and are suitable for application of the product.

The data presented here are based on years of knowledge and experience. We reserve the right to update and/or change them without advance notice.

* The practical spreading rate depends on several factors: the surface, the method of application, the painting shade, the

Tambour Experts Hotline: *6477

www.tambour.co.il

Tambour



Antique Effect

painter's expertise and the prevailing weather conditions at the site. It is common practice to assume that it constitutes approximately 75% of the calculated spreading rate.

** At 25°C and at 65% relative humidity.

Manufactured by Tambour, which has an integrated quality management system compliant with the quality, safety, and environmental requirements according to Standards ISO 14001, ISO 18001, ISO 9001 and has been approved by the Standards Institute of Israel.

For further information please contact the Tambour Experts Hotline at: *6477.

Tambour Experts Hotline: *6477

www.tambour.co.il